

KOČIONI OTPORNICI U ALUMINIJUMSKOM KUĆIŠTU

Otpornik		H (mm)	L (mm)	W (mm)	L1 (mm)	L2 (mm)	D (mm)	ØE (mm)	Priljučni kabl	
Snaga	Otpor								Presek (mm ²)	Dužina (mm)
100W	50Ω	20	140	40	125	105	10	5	2 x 1,5	200
100W	100Ω	20	140	40	125	105	10	5	2 x 1,5	200
100W	150Ω	20	140	40	125	105	10	5	2 x 1,5	200
100W	500Ω	20	140	40	125	105	10	5	2 x 1,5	200
150W	100Ω	20	180	40	165	140	10	5	2 x 1,5	200
150W	150Ω	20	180	40	165	140	10	5	2 x 1,5	200
200W	25Ω	32	170	60	155	110	10	5	2 x 1,5	200
200W	50Ω	32	170	60	155	110	10	5	2 x 1,5	200
200W	100Ω	32	170	60	155	110	10	5	2 x 1,5	200
200W	150Ω	32	170	60	155	110	10	5	2 x 1,5	200
200W	300Ω	32	170	60	155	110	10	5	2 x 1,5	200
250W	120Ω	32	170	60	155	110	10	5	2 x 1,5	200
300W	30Ω	32	220	60	205	160	10	5	2 x 1,5	200
400W	50Ω	32	200	60	205	160	10	5	2 x 1,5	200
400W	80Ω	32	240	60	225	180	10	5	2 x 2,0	200
400W	100Ω	32	240	60	225	180	10	5	2 x 2,0	200
400W	120Ω	32	240	60	225	180	10	5	2 x 2,0	200
400W	150Ω	32	240	60	225	180	10	5	2 x 2,0	200
500W	80Ω	32	240	60	225	240	10	5	2 x 2,0	200

500W	120Ω	32	240	60	225	240	10	5	2 x 2,0	200
500W	150Ω	32	240	60	225	240	10	5	2 x 2,0	200
600W	100Ω	32	240	60	225	240	10	5	2 x 2,0	200
650W	75Ω	32	240	60	225	240	10	5	2 x 2,0	200
800W	80Ω	32	240	60	305	320	10	5	2 x 2,0	200
800W	100Ω	32	240	60	305	320	10	5	2 x 2,0	200
1000W	75Ω	32	240	60	385	340	10	5	2 x 2,5	200
1000W	80Ω	32	240	60	385	340	10	5	2 x 2,5	200
1000W	90Ω	32	400	60	385	340	10	5	2 x 2,5	200